






XF Series

UDF2



Product features:

- Support dual signal & power backup.
- Multiple sealed protection..



Main Technical Specifications:

Parameter	UDF2
Pixel Pitch	2.6mm
LED Type	3-in-1 SMD
Brightness	1,200 cd/m ²
Pixel Density	147,456 pixels/m ²
Pixels Per Panel	192×192 pixels
Module Size	W250mm×H250mm
Panel Size	W500mm×H500mm×D86mm
Weight	14.5 kg/panel
Maintenance	Front (whole cabinet)
Ingress Protection	IP54
Environment	Indoor
Material	Profile & Die-cast Aluminum
Calibration	Support Brightness and Chroma
Brightness Control	Manual/Automatic
Color Temperature	2,000K~9,300K Adjustable
Horizontal Viewing Angle	160°
Vertical Viewing Angle	160°
Contrast Ratio	9,000:1
Input Power <Max>	150 W/panel
Input Power <Typical>	50 W/panel
Input Voltage	100~240 VAC
Processing Depth	14 bit
Scan Method	1/16
Refresh Rate	3,840@60 Hz
Video Frame Rate	50/60 Hz
Input Power Frequency	50~60 Hz

LED Life Time	100,000 Hours
Operating Temperature/Humidity	-10℃~+45℃/10~80%RH
Storage Temperature/Humidity	-20℃~+50℃/10~60%RH
Standard Mounting Configuration	Tiling

Note:

1. The image of the product above is for illustration only and may differ from the actual product (including but not limited to appearance, color, size, etc.).
2. The parameters are reference values, part of which is obtained under a specific test environment in Unilumin' s internal laboratory, there may be slight differences in actual use due to differences in product batch, configuration, software versions, use conditions, and environmental factors.