

## SPECIFICATION PARAMETERS: UTV SC162U

Parameter		UTV SC162U
<b>Basic Parameters</b>	Size (inch)	162
	Display Ratio	16:9
	Resolution (W*H)	3840 (H) x2160(V)
	Pixel Pitch (mm)	0.9375
	Visible Area (㎡)	7.29
	Dimensions (mm)	3611*2151*30.4
	Thickness (mm)	30.4 (without wall-hung) /52.4 (with wall-hung)
	Planeness (mm)	≤0.1
	Weight (kg)	180
	Material	Die-Cast Aluminum
	Border Material/Colour	Aluminum Profile/Dark Gray
	Maintenance	Front
	Installation Method	Wall-mounting, Mobile stand
	<b>Display Parameters</b>	LED Type
LED Life Time (Hrs)		≥100000
Horizontal/Vertical Viewing Angle (degree)		0°~180°
Luminous Point Variation		≤0.30
Brightness (cd/m <sup>2</sup> )		600 (adjustable)
Refresh Rate (Hz)		3840
Video Frame Rate (Hz)		60
Processing Depth (bit)		13
Contrast Ratio		10000:1
Color Temperature (K)		2000~9500
Pixel Level Brightness Calibration	Support	
Pixel Level Color Calibration	Support	

	Brightness Uniformity	≥98%
	Color uniformity	±0.003Cx,Cy or less
	Operating System	Android 11.0
	CPU	Cotex A73*4+A53*4
	RAM/ROM	8GB DDR4 / 64GB
<b>Mainboard Parameters</b>	Interface	SPDIF*1/USB2.0*1/HDMI in*2/USB3.0*3/ Audio out*1/RJ45*2
	WiFi	WiFi 5+ WiFi 6 (Dual wifi)
	Bluetooth	5.0
	Remote Control	Support
<b>Speaker</b>	Fixed mode	Built-in
	Rated power	12Wx2
	Input Voltage	AC 100 V ~ 240 V, 50-60Hz
	Standby Power Consumption (W)	≤0.8
<b>Operation Parameters</b>	Average Power Consumption (W)	876
	Peak Power Consumption (W)	2190
	Operating Temperature/Humidity	-10°C~+45°C/10~80% RH
	Storage Temperature/Humidity	-20°C~+50°C/10~70% RH

## Product accessories:

Category Of Accessories	Name	Quantities
<b>Standard Fittings</b>	Remote Controls	1PC
	U-disk	1PC
	Vacuum Suction Cup	1PC
	Maintenance Tools	1PC
	Spare Parts Module	2PCS
	Other Spare Parts	Several (see shipment list for details)
	Warranty Card	1PC
	Certificate	1PC
	Instructions	1PC
<b>Optional Accessories</b>	Mobile Bracket	1PC
	Dongle (TYPE-C)	(Choose according to the required quantity)